

# E WARM SERIES

## Laminator & Applicator

### Fully Automatic Roll-to-Roll Warm-Assist Laminator

Designed with durable ABS tooling side covers and a precision CNC-machined metal frame for superior strength and stability. The advanced alignment system ensures accurate lamination, delivering consistent, high-quality finishing every time.

Ideal for wide-format laminating and mounting applications, this machine offers reliable performance, ease of operation, and professional results for sign makers, print shops, and graphics production environments.



## Technical Specifications

| MODEL                  | BU-1400E WARM                    | BU-1600E WARM                    | BU-1700E WARM                    |
|------------------------|----------------------------------|----------------------------------|----------------------------------|
| Max. Working Width     | 1400mm(55")                      | 1600mm(63")                      | 1700mm(67")                      |
| Variable Working Speed | 0-6m/min                         | 0-6m/min                         | 0-6m/min                         |
| Max Nip Opening        | 35mm                             | 35mm                             | 35mm                             |
| Max Heat Assist Temp.  | 60°C                             | 60°C                             | 60°C                             |
| Roller Diameter        | 120mm                            | 120mm                            | 120mm                            |
| Top Roller Material    | Silicone Rubber                  | Silicone Rubber                  | Silicone Rubber                  |
| Bottom Roller Material | Natural Rubber                   | Natural Rubber                   | Natural Rubber                   |
| Drive Motor            | AC110V 230V/90W                  | AC110V 230V/90W                  | AC110V 230V/90W                  |
| Power Consumption      | 1300W                            | 1300W                            | 1300W                            |
| Power Requirement      | AC110V/50-60Hz<br>AC230V/50-60Hz | AC110V/50-60Hz<br>AC230V/50-60Hz | AC110V/50-60Hz<br>AC230V/50-60Hz |
| Machine Size           | 1800 x 600 x 1300mm              | 2000 x 600 x 1300mm              | 2100 x 600 x 1300mm              |
| Shipping Dimensions    | 1850 x 630 x 710mm               | 2150 x 710 x 750mm               | 2450 x 710 x 750mm               |
| Weight NW / GW         | 220kg                            | 270kg                            | 280kg                            |

Specifications are subject to change without prior notice.