


K4-32UV

UV Printer



KEDITEC




Main Features



LED Inspection Light Panel




Water Cooling/Drying Technology



Automatic Moisturizing & Cleaning System




1.5L Bulk Ink System with Alarm




High Quality Servo Motor



THK High-Precision Mute Rail



Intelligent Rolling System



3-in-1 Pinch Rollers for Flawless Media Feeding

K4-32UV

UV Printer

Technical Specifications

MODEL		K4-32UV
Print Head		Four I3200-U1 Print Heads
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width	126.7 in.(3220 mm)
	Thickness	Maximum 39 mil(1 mm)
	Weight	176 lb.(80 kg)
Printing Width		125.9 in.(3200 mm)
Ink Cartridges	Type	UV Ink
	Capacity	4*4 CISS (220ml Ink Cartridge with 3L Ink Tank)
	Colour	CMYK CMYK + W CMYK + W + CMYK CMYK LC LM
Printing Resolution		Maximum 2400 dpi
RIP		Onyx / Photoprint
Interface		Network
Power Supply		AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)		181.8(W)x38.1(D)x61.4(H) in. 4620(W)x970(D)x1560(H) mm
Weight(with stand)		1543 lb. (700 kg)
Package Dimensions		188.9(W)x43.3(D)x65.3(H) in. / 4800(W)x1100(D)x1660(H) mm
Package Weight		1763.3 lb. (800 kg)
Environment	Power on	Temperature: 59°F to 90°F [15°C to 32°C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41°F to 104°F [5 °C to 40 °C] / Humidity: 20 to 80% (no condensation)
Accessories		Stand, Media Clamp, Manual, Drain Bottle, Ink Cartridges, RIP Software, Etc.

Specifications are subject to change without prior notice.

Four i3200-U1 Heads

