

K4-32S

Eco Solvent Printer




KEDITEC


Main Features




THK High-Precision Mute Rail



Multi Stage Pinch Roller Structure




High-Stability Tensioning Pulley System



Carriage Anti-Collision Device




Stable 3L Bulk System



Three Stage Heating System



Automated Moisture & Cleaning System



Intelligent Rolling System

K4-32S

Eco Solvent Printer

Technical Specifications

MODEL		K4-32S
Print Head		Four i3200-E1 Print Heads
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width	126.7 in.(3220 mm)
	Thickness	Maximum 39.3 mil(1 mm)
	Weight	176 lb.(80 kg)
Printing Width		125.9 in.(3200 mm)
Ink Cartridges	Type	Eco Solvent Ink
	Capacity	4*4CISS (220ml Ink Cartridge with 3L Ink Tank)
	Colour	CMYK
Printing Resolution		Maximum 2400 dpi
Printing Speed (4 Colours)		4pass(360x2400dpi): 100 m ² /h 6pass(720x1800dpi): 75 m ² /h 8pass(720x2400dpi): 50 m ² /h
Media Heating System		Integrated Post Heater & Infrared Dryer & Fan System
Interface		Network
Power Supply		AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)		181.8(W)x38.1(D)x61.4(H) in. 4620(W)x970(D)x1560(H) mm
Weight(with stand)		1543 lb.(700 kg)
Package Dimensions		188.9(W)x43.3(D)x65.3(H) in. 4800(W)x1100(D)x1660(H) mm
Package Weight		1763.3lb.(800 kg)
Environment	Power on	Temperature: 59°F to 90°F [15°C to 32°C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41°F to 104°F [5 °C to 40 °C] / Humidity: 20 to 80% (no condensation)
Accessories		Stand, Media Loading and Take-up System, Air-cooling System, Bulk Ink Cartridge System, Etc

Specifications are subject to change without prior notice.

Four i3200-E1 Heads

