intamarket GRAPHICS

K32UV

UV DTF Roll to Roll Printer



KEDITEC

Main Features

Plastic

Metal

Glass

Wood

Ceramics

Leather

Suggested Surface Applications

- **Scratch-Resistant & Durable**
- **Strong Adhesion to Most Surfaces**
- **Bright Colour, Good Quality of Finished Products**
- **Waterproof, Lightfast & Dirt-Free**
- **Applicable to Hard, Flat or Curved Surfaces**
- **Metallic Effect with Golden/Silver Colours**

Toll-Free: 0800 110 679 www.intamarketgraphics.co.za inta@intamarket.co.za

K32UV

UV DTF Roll to Roll Printer

intamarket GRAPHICS

Technical Specifications

MODEL		K32UV DTF
Print Technology		2pcs Epson i1600 Print Heads
Printing Head		Piezoelectric Inkjet
Acceptable Media	Width Thickness	≤300 (mm) ≤1.5 (mm)
Ink Cartridges	Capacity Colour	Colour Siphon + White Ink Auto Stirring CMYK + W + Varnish
Printing Resolution		Maximum 2400 dpi
Printing Speed		8pass: 1.5 m^2/h
Ink Curing Method		Dual UV LED Lights
Interface		Gigabit Ethernet
Power Supply		AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)		45.66(W) x 36.2 (D) x 34.6(H) in. 1160(W) x 920(D) x 880(H) mm
Weight(with stand)		441 lb.(200 kg)
Environment	Power on Power off	Temperature: 59°F to 90°F [15°C to 32°C] / Humidity: 35 to 80% (no condensation) Temperature: 41°F to 104°F [5 °C to 40 °C] / Humidity: 20 to 80% (no condensation)

Specifications are subject to change without prior notice.

No Drying Process Required

Good Adhesion on Curved/Rugged Surface

UV Direct Print Effect

No Heating Process Required

KEDITEC UV INK

C M Y K + W + Varnish

Toll-Free: 0800 110 679 www.intamarketgraphics.co.za inta@intamarket.co.za